



LEGENDS

CONTROL AREA	(TMA) (AWY)	
REPORTING POINT	(COMPULSORY)	
REPORTING POINT	(ON REQUEST)	
WAYPOINT	(COMPULSORY / FLY-BY)	
MAGNETIC BEARING	008°	
DEPARTURE/ARRIVAL ROUTING		
DISTANCE IN KILOMETRES		
UPPER LIMIT	8 000	
LOWER LIMIT	2 400	
TRANSIT ROUTE		
RADIO NAVIGATION AID	DANANG DVOR/DME 114.4 DAN 16°03'10"N 108°11'54"E 30 m	

HELICOPTER TRAINING AREAS:

- VVD27
- VVD28
- VVD29
- VVD30

TWR: 118.35 PRI
TWR: 118.05 SRY

APP: 120.45 PRI
APP: 125.45 SRY

CTL: 125.3 PRI
CTL: 125.45 SRY

AREA MINIMUM ALTITUDE (AMA)

EACH 1° QUADRILATERAL CONTAINS AN AREA MINIMUM ALTITUDE (AMA) WHICH REPRESENTS THE LOWEST ALTITUDE WHICH MAY BE USED UNDER INSTRUMENT METEOROLOGICAL CONDITIONS (IMC). THE AMA PROVIDES A MINIMUM CLEARANCE OF 300 METRES (600 METRES IN MOUNTAINOUS AREAS) ABOVE ALL OBSTACLES IN THE QUADRILATERAL. IT IS REPRESENTED IN THOUSANDS AND TENS OF METRES ABOVE MEAN SEA LEVEL.

EXAMPLE: 3 300 METRES **330**

ELEV. ALT IN METRES
DIST IN KILOMETRES
BRG ARE MAG
VAR 1° W

