

STANDARD DEPARTURE CHART – INSTRUMENT (SID) – ICAO

TRANSITION ALTITUDE
2750

APP 120.45 PRI
125.45 SRY
TWR 118.35 PRI
118.05 SRY


**DA NANG/DA NANG INTL (VVDN)
RNAV RWY 35L/R
KONCO 1G, VIDEN 2G, PHULU 1G, BUNTA 2G,
KUMUN 1G, SADIN 1G, XAQUA 1G, PAPRA 2G**

ELEV, ALT IN METRES
DIST IN KILOMETRES
BRG ARE MAG
VAR 1° W

108°00'E

COM FAILURE:

- SET TRANSPONDER CODE 7600.
- CROSS LAIKA / HOKIN / KEMSY / TANNA CLIMBING TO/AT LAST ASSIGNED AND ACKNOWLEDGED FL BUT NOT BELOW MNM FLT ALT*. CONTINUE CLIMB TO FPL FL
- * LEAVE LAST ASSIGNED FL OR ALT AT EARLIEST 7 MIN AFTER IT IS REACHED.



055

030

030

USAGE CONDITION: THESE PROCEDURES ARE ONLY USED IN CASE OF NO MILITARY FLIGHT OPERATION IN RELATED AREAS OR HAVING COMPLETED COORDINATION BETWEEN CIVIL AVIATION AND MILITARY.

NOTES:

1. KUMUN 1G, SADIN 1G, XAQUA 1G, PAPRA 2G: MNM PDG 4.4% UNTIL 502 m.
2. MNM CLIMB GRADIENT (DUE TO ATC OPERATIONAL REQUIREMENT) REFERRED IN CODING TABULAR.

REQUIRED:

1. RNAV 1 (GNSS).
2. ATS SURVEILLANCE.

