

1. TABULAR DESCRIPTION

HUE 1L ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	HUE	–	–	+1	–	–	–	–	RNAV 1
020	TF	HINTA	–	126(125.0)	+1	45.27	–	+2750	–	RNAV 1
030	TF	DN369	–	169(167.8)	+1	16.70	–	-2450 +1850	-420	RNAV 1
040	TF	TAWAN	–	173(172.0)	+1	18.46	–	+1200	-390	RNAV 1

CAHEO 1L ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	CAHEO	–	–	+1	–	–	+FL130	–	RNAV 1
020	TF	HINTA	–	169(167.7)	+1	41.78	–	+2750	–	RNAV 1
030	TF	DN369	–	169(167.8)	+1	16.70	–	-2450 +1850	-420	RNAV 1
040	TF	TAWAN	–	173(172.0)	+1	18.46	–	+1200	-390	RNAV 1

BUNTA 2L ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	BUNTA	–	–	+1	–	–	–	–	RNAV 1
020	TF	KANGU	–	237(235.9)	+1	94.26	–	+FL130	–	RNAV 1
030	TF	HINTA	–	254(252.7)	+1	69.02	–	+2750	–	RNAV 1
040	TF	DN369	–	169(167.8)	+1	16.70	–	-2450 +1850	-420	RNAV 1
050	TF	TAWAN	–	173(172.0)	+1	18.46	–	+1200	-390	RNAV 1

CQ 2L ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	CQ	–	–	+1	–	–	–	–	RNAV 1
020	TF	TAMKY	–	324(322.7)	+1	28.34	–	-2450 +1850	–	RNAV 1
030	TF	TAMLA	–	301(300.2)	+1	38.01	–	+1350	–	RNAV 1

KUMUN 2L ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	KUMUN	–	–	+1	–	–	–	–	RNAV 1
020	TF	NOCKA	–	302(301.3)	+1	95.61	–	+FL100	-410	RNAV 1
030	TF	DAPON	–	028(026.6)	+1	27.16	–	-2450 +1850	–	RNAV 1
040	TF	TAMLA	–	028(026.7)	+1	18.51	–	+1350	–	RNAV 1