

## 1. TABULAR DESCRIPTION

HUE 1N ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	HUE	-	-	+1	-	-	-	-	RNAV 1
020	TF	HUCAO	-	101(100.4)	+1	33.25	-	-	-	RNAV 1
030	TF	LINDA	-	101(100.5)	+1	54.29	-	+FL120	-	RNAV 1
040	TF	KONGA	-	180(179.2)	+1	38.67	-	-1850	-	RNAV 1
050	TF	LOLUC	-	263(262.4)	+1	19.93	-	+1200	-390	RNAV 1

CAHEO 1N ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	CAHEO	-	-	+1	-	-	+FL130	-	RNAV 1
020	TF	HUCAO	-	169(167.7)	+1	21.36	-	-	-	RNAV 1
030	TF	LINDA	-	101(100.5)	+1	54.29	-	+FL120	-	RNAV 1
040	TF	KONGA	-	180(179.2)	+1	38.67	-	-1850	-	RNAV 1
050	TF	LOLUC	-	263(262.4)	+1	19.93	-	+1200	-390	RNAV 1

BUNTA 2N ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	BUNTA	-	-	+1	-	-	-	-	RNAV 1
020	TF	KANGU	-	237(235.9)	+1	94.26	-	+FL130	-	RNAV 1
030	TF	LINDA	-	239(237.7)	+1	19.91	-	+FL120	-	RNAV 1
040	TF	KONGA	-	180(179.2)	+1	38.67	-	-1850	-	RNAV 1
050	TF	LOLUC	-	263(262.4)	+1	19.93	-	+1200	-390	RNAV 1

## 2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
HUE	101(100.0)	+1	1 ≤ FL140 1.5 > FL140	R	+FL100	-425 ≤ FL140 -445 > FL140	RNAV 1
CAHEO	169(168.0)	+1	1 ≤ FL140 1.5 > FL140	R	+FL100	-425 ≤ FL140 -445 > FL140	RNAV 1
KANGU	239(238.0)	+1	1 ≤ FL140 1.5 > FL140	L	+2750	-425 ≤ FL140 -445 > FL140	RNAV 1
LOLUC	264(263.0)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNAV 1