

1. TABULAR DESCRIPTION

INITIAL APPROACH											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	TAWAN	–	–	+1	–	–	+1200	-390	–	RNAV 1
020	TF	KALET	–	082(080.6)	+1	12.79	–	+790	–	–	RNAV 1
010	IF	TAMLA	–	–	+1	–	–	+1350	–	–	RNAV 1
020	TF	KALET	–	352(350.7)	+1	9.56	–	+790	–	–	RNAV 1
010	IF	LOLUC	–	–	+1	–	–	+1200	-390	–	RNAV 1
020	TF	KALET	–	265(263.7)	+1	11.31	–	+790	–	–	RNAV 1

MISSED APPROACH											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	CF	DN353	–	353(352.2)	+1	–	–	–	–	–	RNAV 1
020	TF	DN333	–	039(038.1)	+1	9.10	–	–	–	–	RNAV 1
030	TF	DN555	–	092(090.5)	+1	21.53	–	–	-425	–	RNAV 1
040	TF	KONGA	–	167(166.5)	+1	34.21	–	@1200	–	–	RNAV 1
050	HM	KONGA	–	264(263.0)	+1	–	L	+1200	–	–	RNAV 1

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
LOLUC	264(263.0)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNAV 1
TAMLA	353(352.0)	+1	1 ≤ FL140 1.5 > FL140	R	+1350	-425 ≤ FL140 -445 > FL140	RNAV 1
KONGA	264(263.0)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNAV 1

3. WAYPOINT LIST

WAYPOINT ID/FIX	COORDINATES (WGS-84)
TAMLA (IAF)	15°47'18.0"N 108°14'15.0"E
TAWAN (IAF)	15°51'17.0"N 108°06'19.0"E
LOLUC (IAF)	15°53'05.0"N 108°19'41.0"E
KALET – BRG 173.01° DAD LLZ/D9.61 DAD DME (IF)	15°52'24.8"N 108°13'23.1"E
BRG 173.01° DAD LLZ/D4.56 DAD DME (FAP/FAF)	15°57'26.0"N 108°12'39.4"E
THR RWY 35L – BRG 173.01° DAD LLZ/D0.17 DAD DME (MAPT)	16°01'48.48"N 108°12'01.34"E
DN353	16°08'47.0"N 108°11'02.0"E
DN333	16°12'40.0"N 108°14'11.0"E
DN555	16°12'33.0"N 108°26'16.0"E
KONGA	15°54'31.0"N 108°30'45.0"E
DAD GP/DME	16°01'58.8"N 108°12'03.5"E
DAD LLZ	16°03'36.6"N 108°11'45.7"E