

1. TABULAR DESCRIPTION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	TAWAN	-	-	+1	-	-	+1200	-390	-	RNP APCH
020	TF	KALET	-	082(080.6)	+1	12.79	-	@790	-	-	RNP APCH
010	IF	TAMLA	-	-	+1	-	-	+1350	-	-	RNP APCH
020	TF	KALET	-	352(350.7)	+1	9.56	-	@790	-	-	RNP APCH
010	IF	LOLUC	-	-	+1	-	-	+1200	-390	-	RNP APCH
020	TF	KALET	-	265(263.7)	+1	11.31	-	@790	-	-	RNP APCH
010	IF	KALET	-	-	+1	-	-	@790	-	-	RNP APCH
020	TF	DN351	-	353(352.0)	+1	9.35	-	@450	-	-	RNP APCH
030	TF	RW35L (MAPT)	Y	353(352.0)	+1	8.15	-	@23	-	-3.00°/15.25	RNP APCH
040	CF	DN353	-	353(352.2)	+1	-	-	-	-	-	RNP APCH
050	TF	DN333	-	039(038.1)	+1	9.10	-	-	-	-	RNP APCH
060	TF	DN555	-	092(090.5)	+1	21.53	-	-	-425	-	RNP APCH
070	TF	KONGA	-	167(166.5)	+1	34.21	-	@1200	-	-	RNP APCH
080	HM	KONGA	-	264(263.0)	+1	-	L	+1200	-	-	RNP APCH

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
LOLUC	264(263.0)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
TAMLA	353(352.0)	+1	1 ≤ FL140 1.5 > FL140	R	+1350	-425 ≤ FL140 -445 > FL140	RNP APCH
KONGA	264(263.0)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH

3. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
TAMLA	15°47'18.0"N	108°14'15.0"E
TAWAN	15°51'17.0"N	108°06'19.0"E
LOLUC	15°53'05.0"N	108°19'41.0"E
KALET	15°52'24.8"N	108°13'23.1"E
DN351	15°57'26.0"N	108°12'39.4"E
RW35L	16°01'48.48"N	108°12'01.34"E
DN353	16°08'47.0"N	108°11'02.0"E
DN333	16°12'40.0"N	108°14'11.0"E
DN555	16°12'33.0"N	108°26'16.0"E
KONGA	15°54'31.0"N	108°30'45.0"E