

1. TABULAR DESCRIPTION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	TAWAN	-	-	+1	-	-	+1200	-390	-	RNP APCH
020	TF	FIRAI	-	082(081.2)	+1	13.00	-	@790	-	-	RNP APCH
010	IF	TAMLA	-	-	+1	-	-	+1350	-	-	RNP APCH
020	TF	FIRAI	-	353(352.0)	+1	9.42	-	@790	-	-	RNP APCH
010	IF	LOLUC	-	-	+1	-	-	+1200	-390	-	RNP APCH
020	TF	FIRAI	-	264(263.1)	+1	11.09	-	@790	-	-	RNP APCH
010	IF	FIRAI	-	-	+1	-	-	@790	-	-	RNP APCH
020	TF	DN352	-	353(352.0)	+1	9.35	-	@450	-	-	RNP APCH
030	TF	RW35R (MAPT)	Y	353(352.0)	+1	8.13	-	@24	-	-3.00°/15.25	RNP APCH
040	CF	DN354	-	353(352.1)	+1	-	-	-	-	-	RNP APCH
050	TF	DN333	-	037(035.5)	+1	9.25	-	-	-	-	RNP APCH
060	TF	DN555	-	092(090.5)	+1	21.53	-	-	-425	-	RNP APCH
070	TF	KONGA	-	167(166.5)	+1	34.21	-	@1200	-	-	RNP APCH
080	HM	KONGA	-	264(263.0)	+1	-	L	+1200	-	-	RNP APCH

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
LOLUC	264(263.0)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
TAMLA	353(352.0)	+1	1 ≤ FL140 1.5 > FL140	R	+1350	-425 ≤ FL140 -445 > FL140	RNP APCH
KONGA	264(263.0)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH

3. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
LOLUC	15°53'05.0"N	108°19'41.0"E
TAMLA	15°47'18.0"N	108°14'15.0"E
TAWAN	15°51'17.0"N	108°06'19.0"E
FIRAI	15°52'21.5"N	108°13'30.9"E
DN352	15°57'22.6"N	108°12'47.2"E
RW35R	16°01'44.57"N	108°12'09.17"E
DN354	16°08'35.0"N	108°11'10.0"E
DN333	16°12'40.0"N	108°14'11.0"E
DN555	16°12'33.0"N	108°26'16.0"E
KONGA	15°54'31.0"N	108°30'45.0"E