

Procedure coding

1. ILS W RWY 17

INITIAL APPROACH SEGMENT

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
1	IF	BUXEN	-	-	+1	-	-	+900	-	-	RNP 1
2	TF	VAMLU	-	337 (335.7)	+1	40.9	-	-	-	-	RNP 1
3	TF	VH171	-	264 (262.6)	+1	13.0	-	@900	-	-	RNP 1

MISSED APPROACH SEGMENT

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
1	CA	-	-	174 (172.6)	+1	-	-	+150	-	-	RNP 1
2	DF	BUXEN	-	-	+1	-	-	@900	-	-	RNP 1
3	HM	BUXEN	-	337 (335.7)	+1	-	R	+900	-	-	RNP 1

2. HOLDING PROCEDURE

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
BUXEN	337 (335.7)	+1	1 ≤ FL140 1.5 > FL140	R	+900	-425 ≤ FL140 -445 > FL140	RNP 1