

# Procedure coding

## 1. ILS W RWY 09: INITIAL APPROACH SEGMENT FROM DL501

RCMD.PATH TEMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV SPEC
IF	DL501	-	-	-	-	1850	-	-	RNP 1
TF	DL902	-	29.2	310°(309.9°)	-	1850	-	-	RNP 1
TF	DL900	-	9.3	357°(356.9°)	R	@1810	-	-	RNP 1

## 2. ILS W MISSED APPROACH PROCEDURE RWY 09

RCMD.PATH TEMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (KM)	MAG TRACK (TRUE TRACK)	TURN DIRECTION	ALTITUDE (M)	SPEED LIMIT (IAS) KM/H	VER ANGLE	NAV SPEC
IF	MAPT	Y	-	-	-	-	-	-	RNP 1
FA	-	-	-	087°(086.9°)	-	1280	-	-	RNP 1
DF	DL501	-	-	-	R	1850	-	-	RNP 1
HM	DL501	Y	-	310°(309.9°)	L	+1850	-	-	RNP 1

## 3. RNP HOLDING PROCEDURE

Holding Fix	Fly- over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
DL501	Y	310°(309.9°)	0°	1 ≤ FL140 1.5 > FL140	L	+1850	-430 ≤ FL140 -445 > FL140	RNP 1