

Procedure coding

1. RNP 1 RWY 09: KANAM TWO ECHO DEPARTURE (KANAM 2E)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	DL209	-	087 (086.9)	0	13.0	-	+1500	-	RNP 1
2	TF	KANAM	-	062 (062.0)	0	16.8	L	+2450	-	RNP 1

KARDA 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	KANAM	-	-	0	-	-	+2450	-	RNP 1
2	TF	KARDA	-	074 (074.2)	0	20.0	R	+FL110	-	RNP 1

2. RNP 1 RWY 09: KILEN ONE ALPHA DEPARTURE (KILEN 1A)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	DL209	-	087 (086.9)	0	13.0	-	+1500	-430	RNP 1
2	TF	DL219	-	357 (356.8)	0	13.0	L	-	-	RNP 1
3	TF	KILEN	-	332 (331.7)	0	18.1	L	-FL110 +2750	-	RNP 1

BMT 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	KILEN	-	-	0	-	-	-FL110 +2750	-	RNP 1
2	TF	MIMEN	-	346 (346.0)	0	21.0	R	-	-	RNP 1
3	TF	BMT	-	333 (332.9)	0	57.3	L	-	-	RNP 1

3. RNP 1 RWY 09: GIVIK ONE ALPHA DEPARTURE (GIVIK 1A)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	DL209	-	087 (086.9)	0	13.0	-	+1500	-430	RNP 1
2	TF	DL239	-	177 (176.9)	0	13.0	R	-FL110 +2750	-430	RNP 1
3	TF	DL259	-	244 (243.5)	0	12.3	R	+FL110	-	RNP 1
4	TF	GIVIK	-	244 (243.5)	0	19.7	-	+FL130	-	RNP 1

VETOM 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	GIVIK	-	-	0	-	-	+FL130	-	RNP 1
2	TF	VETOM	-	246 (245.8)	0	75.6	-	-	-	RNP 1