

# Procedure coding

## 1. RNP 1 RWY 27: HONGA TWO ECHO DEPARTURE (HONGA 2E)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	VA	-	-	267 (266.9)	0	-	-	@1200	-	RNP 1
2	DF	HONGA	-	-	0	-	R	-FL110 +2450	-	RNP 1

MIN PDG 4.3% UNTIL REACHING 1250m.

## 2. RNP 1 RWY 27: SAGUL ONE ALPHA DEPARTURE (SAGUL 1A)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	SAGUL	-	267 (266.9)	0	27.7	-	-3050 +1850	-	RNP 1

## VETOM 1B TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	SAGUL	-	-	0	-	-	-3050 +1850	-	RNP 1
2	TF	VETOM	-	224 (223.5)	0	77.1	-	-	-	RNP 1

## 3. RNP 1 RWY 27: RANGA ONE ALPHA DEPARTURE (RANGA 1A)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	DL027	-	267 (267.0)	0	8.8	-	-	-430	RNP 1
2	TF	DL127	-	193 (193.4)	0	14.6	L	+2150	-	RNP 1
3	TF	DL227	Y	162 (162.4)	0	13.0	L	-2450	-440	RNP 1
4	TF	RANGA	-	080 (080.0)	0	31.8	L	+FL110	-460	RNP 1

## CRA 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	RANGA	-	-	0	-	-	+FL110	-	RNP 1
2	TF	CRA	-	056 (056.1)	0	86.8	L		-	RNP 1