

Procedure coding (cont.)

TANOS 2A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TANOS	-	-	0	-	-	-	-	RNP 1
2	TF	DL640	-	042 (042.1)	0	104.8	-	-	-	RNP 1
3	TF	DILIN	-	042 (042.2)	0	27.8	-	+2450	-	RNP 1

VETOM 2C TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	VETOM	-	-	0	-	-	-	-	RNP 1
2	TF	DL630	-	055 (054.7)	0	43.2	-	-	-	RNP 1
3	TF	DILIN	-	055 (054.7)	0	27.8	-	+2450	-	RNP 1

5. RNP HOLDING PROCEDURE

Holding Fix	Fly-over	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
DILIN	Y	026°(025.7°)	0	1 ≤ FL140	L	-3050 +2450	-430 ≤ FL140	RNP 1
ROZAN	Y	178°(177.8°)	0	1 ≤ FL140 1.5 > FL140	R	+2450	-430 ≤ FL140 -445 > FL140	RNP 1
HONGA	Y	184°(184.0°)	0	1 ≤ FL140 1.5 > FL140	L	+FL110	-430 ≤ FL140 -445 > FL140	RNP 1
LKH	Y	254°(254.0°)	0	1 ≤ FL140 1.5 > FL140	R	+FL120	-430 ≤ FL140 -445 > FL140	RNP 1