

## Take-off minima for RWY 09/27

Take-off for RWY 09/27	ACFT CAT	RVR (M)	Visibility (M)
	A, B	2 000	2 000
	C, D	2 500	2 500

- Note:**
1. Take-off alternate aerodromes: Tan Son Nhat, Da Nang, Buon Ma Thuot, Cam Ranh.
  2. When take-off alternate aerodrome cannot be chosen, the operational minima for take-off will be the value for landing as appropriate.

## Landing minima for RWY 09/27

VOR approach procedure for RWY 09	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	210		3 000
	C, D	210		3 500

ILS approach procedure for RWY 09	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	160	2 000	2 000

ILS approach procedure for RWY 09 (in case of GP unserviceable)	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	240		3 000
	C, D	240		3 500

ILS X, ILS W approach procedure for RWY 09	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	160	1 600	1 900

ILS X, ILS W approach procedure for RWY 09 (in case of GP unserviceable)	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	210		2 800

RNP Z, Y (LNAV) approach procedure for RWY 09	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	240		3 400