

# Procedure coding

## 1. BUXEN ONE JULIETT ARRIVAL (BUXEN 1J)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
1	IF	BUXEN	-	-	+1	-	-	+FL110	-	RNAV 1
2	TF	BIDUM	-	337 (335.7)	+1	28.0	-	@2150	-365	RNAV 1
3	TF	VH804	-	051 (050.3)	+1	6.9	-	-	-	RNAV 1
4	TF	VH803	-	020 (019.4)	+1	6.9	-	-	-	RNAV 1
5	TF	VH802	-	349 (347.8)	+1	6.9	-	-	-	RNAV 1
6	TF	VH801	-	319 (318.5)	+1	6.9	-	@2150	-365	RNAV 1
7	TF	VAMLU	-	213 (212.2)	+1	13.0	-	@1500	-365	RNAV 1

## KAMSU 1H TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
1	IF	KAMSU	-	-	+1	-	-	-	-	RNAV 1
2	TF	BUXEN	-	337 (335.8)	+1	43.1	-	+FL110	-	RNAV 1

## 2. TEBIR ONE JULIETT ARRIVAL (TEBIR 1J)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
1	IF	TEBIR	-	-	+1	-	-	@2750	-	RNAV 1
2	TF	DOMPU	-	195 (194.4)	+1	33.9	-	@1500	-410	RNAV 1
3	TF	VH914	-	108 (106.8)	+1	9.9	-	-	-	RNAV 1
4	TF	VH913	-	139 (137.7)	+1	9.9	-	-	-	RNAV 1
5	TF	VH912	-	170 (168.6)	+1	9.9	-	-	-	RNAV 1
6	TF	VH911	-	200 (199.4)	+1	9.9	-	@1500	-410	RNAV 1
7	TF	VAMLU	-	306 (304.9)	+1	18.5	-	@1500	-390	RNAV 1

## NAH 1H TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
1	IF	NAH	-	-	+1	-	-	-	-	RNAV 1
2	TF	TEBIR	-	196 (194.5)	+1	111.8	-	@2750	-	RNAV 1

## 3. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
BUXEN	337 (335.8)	+1	1 ≤ FL140 1.5 > FL140	R	+FL110	-425 ≤ FL140 -445 > FL140	RNAV 1
TEBIR	195 (194.4)	+1	1 ≤ FL140 1.5 > FL140	L	+2750	-425 ≤ FL140 -445 > FL140	RNAV 1