

Procedure coding

1. BUXEN ONE HOTEL ARRIVAL (BUXEN 1H)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
1	IF	BUXEN	-	-	+1	-	-	+FL110	-	RNP 1
2	TF	BIDUM	-	337 (335.7)	+1	28.0	-	@2150	-	RNP 1
3	TF	VAMLU	-	337 (335.7)	+1	13.0	-	@1500	-	RNP 1

KAMSU 1H TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
1	IF	KAMSU	-	-	+1	-	-	-	-	RNP 1
2	TF	BUXEN	-	337 (335.8)	+1	43.1	-	+FL110	-	RNP 1

2. GUKAL ONE HOTEL ARRIVAL (GUKAL 1H)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
1	IF	GUKAL	-	-	+1	-	-	-2150 +1500	-	RNP 1
2	TF	DOXAT	-	060 (058.7)	+1	12.7	-	+1200	-	RNP 1

IDOTA 1H TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
1	IF	IDOTA	-	-	+1	-	-	+FL130	-	RNP 1
2	TF	GUKAL	-	060 (058.6)	+1	34.6	-	-2150 +1500	-	RNP 1

3. TEBIR ONE HOTEL ARRIVAL (TEBIR 1H)

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
1	IF	TEBIR	-	-	+1	-	-	@2750	-	RNP 1
2	TF	DOMPU	-	195 (194.4)	+1	33.9	-	@1500	-	RNP 1
3	TF	BAXIK	-	214 (213.4)	+1	14.9	-	+900	-	RNP 1

NAH 1H TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
1	IF	NAH	-	-	+1	-	-	-	-	RNP 1
2	TF	TEBIR	-	196 (194.5)	+1	111.8	-	@2750	-	RNP 1

4. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
BUXEN	337 (335.8)	+1	1 ≤ FL140 1.5 > FL140	R	+FL110	-425 ≤ FL140 -445 > FL140	RNP 1
TEBIR	195 (194.4)	+1	1 ≤ FL140 1.5 > FL140	L	+2750	-425 ≤ FL140 -445 > FL140	RNP 1