

1. TABULAR DESCRIPTION

INITIAL APPROACH

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	VIPID	–	–	+1	–	–	+1500	-380	–	RNP 1
020	TF	DH802	–	298(296.7)	+1	12.96	–	@900	–	–	RNP 1
010	IF	ISVAM	–	–	+1	–	–	+1500	-380	–	RNP 1
020	TF	DH802	–	205(204.2)	+1	12.96	–	@900	–	–	RNP 1

MISSED APPROACH

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	FA	RWY29	–	295(294.1)	+1	–	–	+450	–	–	RNP 1
020	DF	DONGI	–	–	+1	–	R	@900	-360	–	RNP 1
030	HM	DONGI	–	123(122.0)	+1	–	L	+900	-360	–	RNP 1

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
DONGI	123(122.0)	+1	1 ≤ FL140 1.5 > FL140	L	+900	-360	RNP 1

3. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
DONGI	17°40'53.0"N	106°35'43.0"E
ISVAM	17°32'28.5"N	106°49'44.8"E
VIPID	17°22'54.1"N	106°53'17.4"E
MAPT	17°29'56.8"N	106°37'42.6"E
BRG 115.07° IDH LLZ/D1.61 IDH GP/DME	17°28'07.8"N	106°41'56.4"E
DH801 (FAP/FAF)	17°26'03.7"N	106°46'45.1"E
BRG 115.08° IDH LLZ/D11.08 IDH GP/DME	17°30'39.6"N	106°36'11.7"E
IDH GP/DME	17°31'08.2"N	106°34'56.0"E
IDH LLZ	17°30'32.39"N	106°36'19.47"E
RWY29		