

1. TABULAR DESCRIPTION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	DONGI	-	-	+1	-	-	+900	-360	-	RNP APCH
020	TF	ISVAM	-	123(122.0)	+1	29.27	-	-	-	-	RNP APCH
030	TF	DH802	-	205(204.2)	+1	12.96	-	@900	-	-	RNP APCH
040	TF	DH800	-	295(294.1)	+1	9.28	-	@600	-	-	RNP APCH
050	TF	RWY29 (MAPT)	Y	295(294.1)	+1	10.94	-	@26	-	-3.0/15.25	RNP APCH
060	FA	RWY29	-	295(294.1)	+1	-	-	+450	-	-	RNP APCH
070	DF	DONGI	-	-	+1	-	R	@900	-360	-	RNP APCH
080	HM	DONGI	-	123(122.0)	+1	-	L	+900	-360	-	RNP APCH

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
DONGI	123(122.0)	+1	1 ≤ FL140 1.5 > FL140	L	+900	-360	RNP APCH

3. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
DH800	17°28'07.1"N	106°41'58.1"E
DH802	17°26'03.7"N	106°46'45.1"E
DONGI	17°40'53.0"N	106°35'43.0"E
ISVAM	17°32'28.5"N	106°49'44.8"E
RWY29	17°30'32.39"N	106°36'19.47"E