

**Procedure coding**

**1. RNP Z RWY 27**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	PB402	-	-	+1.0	-	-	+1200	-	-	RNP APCH
020	TF	PB401	-	184°(183.2°)	+1.0	13.0	-	@750	-	-	RNP APCH
030	TF	PB400	-	274°(273.2°)	+1.0	9.6	R	@500	-	-	RNP APCH
040	TF	PB600 (MAPT)	Y	274°(273.2°)	+1.0	7.2	-	@125	-	-3.0/15.25	RNP APCH
050	DF	PB601	-	-	+1.0	-	-	-	-	-	RNP APCH
060	TF	PB602	-	004°(003.2°)	+1.0	27.8	R	@900	-	-	RNP APCH
070	HM	PB602	-	-	+1.0	-	L	+900	-	-	RNP APCH

**2. MISSED APPROACH TRANSITION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/ TCH	Nav Spec
010	IF	PB602	-	-	+1.0	-	-	+900	-	-	RNP 1
020	TF	PB402	-	124°(122.7°)	+1.0	30.1	-	+1200	-	-	RNP 1

**3. HOLDING PROCEDURES**

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PB402	184°(183.2°)	+1.0	1 ≤ FL140 1.5 > FL140	L	+1200	-430 ≤ FL140 -445 > FL140	RNP 1
PB602	124°(122.7°)	+1.0	1 ≤ FL140 1.5 > FL140	L	+900	-430 ≤ FL140 -445 > FL140	RNP 1