

Procedure coding

1. RNP 1 RWY 09: XILGA ONE ALPHA DEPARTURE (XILGA 1A)

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|---------------|--------------|----------|
| 1 | CF | PB109 | Y | 094 (093.2) | +1.0 | 13.0 | - | -1200 +900 | - | RNP 1 |
| 2 | TF | XILGA | - | 094 (093.2) | +1.0 | 15.5 | - | +1850 | - | RNP 1 |

DAN 1B TRANSITION

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|------------------|--------------|----------|
| 1 | IF | XILGA | - | - | +1.0 | - | - | +1850 | - | RNP 1 |
| 2 | TF | DAN | - | 149 (147.9) | +1.0 | 43.4 | R | -FL130 +FL120 | - | RNP 1 |

2. RNP 1 RWY 09: NAKHE ONE BRAVO DEPARTURE (NAKHE 1B)

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|---------------|--------------|----------|
| 1 | CF | PB109 | Y | 094 (093.2) | +1.0 | 13.0 | - | -1200 +900 | -440 | RNP 1 |
| 2 | DF | PB209 | - | - | +1.0 | - | L | +2150 | - | RNP 1 |
| 3 | TF | PB309 | - | 275 (274.4) | +1.0 | 15.0 | L | +2750 | -450 | RNP 1 |
| 4 | TF | PB409 | - | 196 (195.0) | +1.0 | 19.2 | L | +FL110 | - | RNP 1 |
| 5 | TF | NAKHE | - | 196 (195.0) | +1.0 | 28.8 | - | - | - | RNP 1 |

SADIN 1C TRANSITION

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1 | IF | NAKHE | - | - | +1.0 | - | - | - | - | RNP 1 |
| 2 | TF | SADIN | - | 153 (152.1) | +0.7 | 134.0 | - | +FL120 | - | RNP 1 |

VILOT 1B TRANSITION

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1 | IF | NAKHE | - | - | +1.0 | - | - | - | - | RNP 1 |
| 2 | TF | VILOT | - | 156 (155.7) | +0.7 | 135.1 | - | +FL120 | - | RNP 1 |