

## Procedure coding (cont.)

### LATOM 1B TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	LATOM	-	-	+0.7	-	-	-	-	RNP 1
2	TF	NOCKA	-	021 (020.0)	+0.7	63.7	-	+FL100	-	RNP 1
3	TF	VIDAN	-	353 (352.0)	+0.7	37.1	L	-FL160	-	RNP 1
4	TF	PHADE	-	338 (337.2)	+1.0	48.4	L	-FL100 +2450	-	RNP 1

### SADIN 1D TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	SADIN	-	-	+0.7	-	-	-	-	RNP 1
2	TF	NOCKA	-	340 (339.5)	+0.7	40.1	-	+FL100	-	RNP 1
3	TF	VIDAN	-	353 (352.0)	+0.7	37.1	R	-FL160	-	RNP 1
4	TF	PHADE	-	338 (337.2)	+1.0	48.4	L	-FL100 +2450	-	RNP 1

### VILOT 1C TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	VILOT	-	-	+0.7	-	-	-	-	RNP 1
2	TF	NOCKA	-	351 (350.6)	+0.7	42.7	-	+FL100	-	RNP 1
3	TF	VIDAN	-	353 (352.0)	+0.7	37.1	R	-FL160	-	RNP 1
4	TF	PHADE	-	338 (337.2)	+1.0	48.4	L	-FL100 +2450	-	RNP 1

### KUMUN 1C TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	KUMUN	-	-	+0.7	-	-	-	-	RNP 1
2	TF	NOCKA	-	302 (301.3)	+0.7	95.7	-	+FL100	-	RNP 1
3	TF	VIDAN	-	353 (352.0)	+0.7	37.1	R	-FL160	-	RNP 1
4	TF	PHADE	-	338 (337.2)	+1.0	48.4	L	-FL100 +2450	-	RNP 1

### DAN 1A TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	DAN	-	-	+1.0	-	-	+FL140	-	RNP 1
2	TF	PHADE	-	287 (285.7)	+1.0	41.7	-	-FL100 +2450	-	RNP 1

### 3. RNP HOLDING PROCEDURE

Holding Fix	Fly-over	Inbound Course/ Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PHADE	Y	296°(294.5°)	+1.0	1 ≤ FL140 1.5 > FL140	L	+2450	-430 ≤ FL140 -445 > FL140	RNP 1
PHADE	Y	335°(334.3°)	+1.0	1 ≤ FL140 1.5 > FL140	R	+2450	-430 ≤ FL140 -445 > FL140	RNP 1
PB093	Y	185°(183.9°)	+1.0	1 ≤ FL140 1.5 > FL140	R	+1200	-430 ≤ FL140 -445 > FL140	RNP 1
PB094	Y	296°(294.5°)	+1.0	1 ≤ FL140 1.5 > FL140	L	+1850	-430 ≤ FL140 -445 > FL140	RNP 1