

### 1. TABULAR DESCRIPTION

BODOD 2F ARRIVAL											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	BODOD	-	-	0	-	-	-	-	-	RNP 1
020	TF	NIXIV	-	222(222.1)	0	36.70	-	-FL120	-	-	RNP 1
030	TF	CS415	-	200(200.0)	0	27.03	-	-2450	-	-	RNP 1
040	TF	CONDA	-	200(199.9)	0	24.28	-	-1500	-	-	RNP 1
050	TF	CS413	-	189(188.6)	0	6.96	-	+1200	-	-	RNP 1

NIXIV 2F ARRIVAL											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	NIXIV	-	-	0	-	-	-FL120	-	-	RNP 1
020	TF	CS415	-	200(200.0)	0	27.03	-	-2450	-	-	RNP 1
030	TF	CONDA	-	200(199.9)	0	24.28	-	-1500	-	-	RNP 1
040	TF	CS413	-	189(188.6)	0	6.96	-	+1200	-	-	RNP 1

VEPKI 1F ARRIVAL											
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	VEPKI	-	-	0	-	-	-	-	-	RNP 1
020	TF	CONDA	-	146(145.9)	0	19.84	-	-1500	-	-	RNP 1
030	TF	CS413	-	189(188.6)	0	6.96	-	+1200	-	-	RNP 1

### 2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
CS413	188(188.4)	0	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNP 1

### 3. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
BODOD	09°38'22"N	106°51'29"E
CONDA	08°57'26"N	106°28'29"E
CS413	08°53'42"N	106°27'55"E
CS415	09°09'49"E	106°33'00"E
NIXIV	09°23'36"N	106°38'02"E
VEPKI	09°06'21"N	106°22'25"E