

Procedure coding

1. RNP Y RWY 15

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	PC901	-	-	+1	-	-	+1200	-	-	RNP APCH
2	TF	PC402	-	289 (288.2)	+1	33.0	-	-	-390	-	RNP APCH
3	TF	PC401	-	268 (266.7)	+1	13.0	-	@1050	-350	-	RNP APCH
4	TF	PC400	-	178 (176.6)	+1	9.3	-	@750	-	-	RNP APCH
5	TF	RWY15 (MAPT)	Y	148 (146.6)	+1	11.6	-	@43	-	-3.5/ 15.25	RNP APCH
6	CF	PC600	-	148 (146.7)	+1	-	-	-	-	-	RNP APCH
7	TF	PC901	-	063 (062.0)	+1	36.6	-	@1200	-	-	RNP APCH
8	HM	PC901	-	289 (288.2)	+1	-	R	+1200	-	-	RNP APCH

2. HOLDING PROCEDURES

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PC901	289 (288.2)	+1	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH