

Procedure coding

1. ILS Z RWY 33

INITIAL APPROACH SEGMENT FROM PC711

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	PC711	-	-	+1	-	-	-2150 +1500	-390	-	RNP 1
2	TF	PC701	-	057 (056.1)	+1	13.0	-	@900	-	-	RNP 1

INITIAL APPROACH SEGMENT FROM PC721

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	PC721	-	-	+1	-	-	-2150 +1500	-	-	RNP 1
2	TF	PC701	-	010 (009.1)	+1	13.0	-	@900	-	-	RNP 1

INITIAL APPROACH SEGMENT FROM PC731

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	IF	PC731	-	-	+1	-	-	+1200	-390	-	RNP 1
2	TF	PC701	-	237 (236.2)	+1	9.3	-	@900	-	-	RNP 1

MISSED APPROACH SEGMENT

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	VPA	Nav Spec
1	CF	PC800	-	328 (327.0)	+1	-	-	-	-	-	RNP 1
2	TF	PC801	-	030 (029.0)	+1	11.7	-	-	-	-	RNP 1
3	TF	PC821	-	092 (091.0)	+1	15.4	-	-	-	-	RNP 1
4	TF	PC901	-	110 (108.9)	+1	21.8	-	@1200	-	-	RNP 1
5	HM	PC901	-	217 (216.1)	+1	-	L	+1200	-	-	RNP 1

2. HOLDING PROCEDURES

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PC711	057 (056.1)	+1	1 ≤ FL140 1.5 > FL140	R	+1850	-425 ≤ FL140 -445 > FL140	RNP 1
PC721	010 (009.1)	+1	1 ≤ FL140 1.5 > FL140	R	+1500	-425 ≤ FL140 -445 > FL140	RNP 1
PC731	237 (236.2)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP 1
PC901	217 (216.1)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP 1