

Procedure coding

1. RNP Y RWY 33

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | VPA | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|--------------|--------------|----------------|----------|
| 1 | IF | PC901 | - | - | +1 | - | - | +1200 | - | - | RNP APCH |
| 2 | TF | PC731 | - | 217 (216.1) | +1 | 29.0 | - | - | -390 | - | RNP APCH |
| 3 | TF | PC701 | - | 237 (236.2) | +1 | 9.3 | - | @900 | - | - | RNP APCH |
| 4 | TF | PC700 | - | 328 (326.6) | +1 | 9.3 | - | @600 | - | - | RNP APCH |
| 5 | TF | RWY33 (MAPT) | Y | 328 (326.6) | +1 | 10.7 | - | @41 | - | -3.0/ 15.25 | RNP APCH |
| 6 | CF | PC800 | - | 328 (326.7) | +1 | - | - | - | - | - | RNP APCH |
| 7 | TF | PC801 | - | 030 (029.0) | +1 | 11.7 | - | - | - | - | RNP APCH |
| 8 | TF | PC821 | - | 092 (091.0) | +1 | 15.4 | - | - | - | - | RNP APCH |
| 9 | TF | PC901 | - | 110 (108.9) | +1 | 21.8 | - | @1200 | - | - | RNP APCH |
| 10 | HM | PC901 | - | 217 (216.1) | +1 | - | L | +1200 | - | - | RNP APCH |

2. HOLDING PROCEDURES

| Holding Fix | Inbound Course/Track °M(°T) | Magnetic Variation | Time (min) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|-------------|-----------------------------|--------------------|--------------------------|----------------|--------------|------------------------------|----------|
| PC901 | 217 (216.1) | +1 | 1 ≤ FL140 1.5 > FL140 | L | +1200 | -425 ≤ FL140 -445 > FL140 | RNP APCH |