

Procedure coding

1. KUMUN 1C DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	PC500	-	148 (146.7)	+1	-	-	-	-	3.4	RNP 1
2	TF	PC511	-	058 (056.6)	+1	14.2	-	-1850 +900	-	3.4	RNP 1
3	TF	PC512	-	358 (356.7)	+1	28.4	-	-	-	4.5	RNP 1
4	TF	DOXIS	-	334 (333.2)	+1	40.3	-	+FL130	-	4.5	RNP 1
5	TF	PC999	-	326 (324.9)	+1	34.0	-	-	-	-	RNP 1
6	TF	KUMUN	-	348 (347.3)	+1	25.1	-	-	-	-	RNP 1

2. KAMGO 1C DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	PC500	-	148 (146.7)	+1	-	-	-	-	3.7	RNP 1
2	TF	PC531	-	148 (146.7)	+1	20.5	-	-1850 +1200	-	3.7	RNP 1
3	TF	VINIX	-	182 (180.7)	+1	27.8	-	-FL120 +FL100	-	6.7	RNP 1
4	TF	KAMGO	-	217 (215.9)	+1	21.1	-	-	-	-	RNP 1

3. NOBID 1M DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	PC500	-	148 (146.7)	+1	-	-	-	-	5.6	RNP 1
2	TF	PC521	-	216 (215.3)	+1	9.3	-	-1850 +1200	-	5.6	RNP 1
3	TF	PC522	-	216 (215.2)	+1	17.2	-	-2450 +1850	-	3.8	RNP 1
4	TF	NINOV	-	216 (215.2)	+1	26.6	-	-FL120 +2450	-	-	RNP 1
5	TF	NOBID	-	241 (239.6)	+1	31.4	-	-	-	-	RNP 1