

# Procedure coding

## 1. KUMUN 1F ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	KUMUN	-	-	+1	-	-	-	-	RNP 1
2	TF	VEXIT	-	168 (167.3)	+1	55.1	-	-FL110 +2450	-	RNP 1
3	TF	DEMIS	-	168 (167.2)	+1	30.0	-	+1500	-	RNP 1

## 2. KAMGO 1F ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	KAMGO	-	-	+1	-	-	-	-	RNP 1
2	TF	XIKRA	-	356 (355.1)	+1	14.4	-	+FL130	-	RNP 1
3	TF	PC405	-	002 (000.7)	+1	52.6	-	+2750	-	RNP 1
4	TF	PC403	-	002 (000.7)	+1	15.0	-	+2150	-	RNP 1
5	TF	PC402	-	358 (356.7)	+1	13.0	-	+1200	-390	RNP 1

## 3. NOBID 1P ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	NOBID	-	-	+1	-	-	-	-	RNP 1
2	TF	SEGTO	-	036 (034.9)	+1	27.0	-	+FL130	-	RNP 1
3	TF	PC403	-	036 (035.3)	+1	69.8	-	+2150	-	RNP 1
4	TF	PC402	-	358 (356.7)	+1	13.0	-	+1200	-390	RNP 1

## 4. HOLDING PROCEDURES

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
VEXIT	168 (167.2)	+1	1 ≤ FL140 1.5 > FL140	L	+2450	-425 ≤ FL140 -445 > FL140	RNP 1
XIKRA	002 (000.7)	+1	1 ≤ FL140 1.5 > FL140	L	+FL130	-425 ≤ FL140 -445 > FL140	RNP 1
SEGTO	036 (035.3)	+1	1 ≤ FL140 1.5 > FL140	R	+FL130	-425 ≤ FL140 -445 > FL140	RNP 1
DEMIS	188 (187.3)	+1	1 ≤ FL140 1.5 > FL140	L	+1500	-425 ≤ FL140 -445 > FL140	RNP 1
PC402	268 (266.7)	+1	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNP 1