

**1. TABULAR DESCRIPTION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	CS413	-	-	0	-	-	+1200	-	-	RNP APCH
020	TF	CS412	-	188(188.4)	0	11.12	-	@900	-	-	RNP APCH
010	IF	CS500	-	-	0	-	-	+1200	-	-	RNP APCH
020	TF	CS414	-	320(320.5)	0	24.82	-	-	-	-	RNP APCH
030	TF	CS412	-	019(019.4)	0	9.28	-	@900	-	-	RNP APCH
010	IF	CS412	-	-	0	-	-	@900	-	-	RNP APCH
020	TF	CS411	-	109(109.3)	0	9.26	-	@600	-	-	RNP APCH
030	TF	RWY11 (MAPT)	Y	109(109.3)	0	11.06	-	@21	-	-3.00°/15.25	RNP APCH
040	CF	CS410	-	109(109.3)	0	-	-	-	-	-	RNP APCH
050	TF	CS409	-	194(194.4)	0	13.39	-	-	-	-	RNP APCH
060	TF	CS500	-	246(245.8)	0	12.74	-	@1200	-	-	RNP APCH
070	HM	CS500	-	320(320.0)	0	-	L	+1200	-	-	RNP APCH

**2. HOLDING PROCEDURES**

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
CS413	188(188.4)	0	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
CS500	320(320.0)	0	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH

**3. WAYPOINT LIST**

WAYPOINT ID	COORDINATES (WGS-84)	
CS409	08°35'26.0"N	106°40'18.0"E
CS410	08°42'28.0"N	106°42'07.0"E
CS411	08°46'04.2"N	106°31'47.9"E
CS412	08°47'43.9"N	106°27'02.0"E
CS413	08°53'42.0"N	106°27'55.0"E
CS414	08°42'59.0"N	106°25'21.0"E
CS500	08°32'36.0"N	106°33'58.0"E
RWY11	08°44'05.01"N	106°37'29.24"E