

1. TABULAR DESCRIPTION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	CS613	-	-	0	-	-	+1200	-	-	RNP APCH
020	TF	CS612	-	199(199.5)	0	11.11	-	@900	-	-	RNP APCH
010	IF	CS500	-	-	0	-	-	+1200	-	-	RNP APCH
020	TF	CS614	-	080(080.3)	0	26.43	-	-	-	-	RNP APCH
030	TF	CS612	-	019(019.3)	0	9.27	-	@900	-	-	RNP APCH
010	IF	CS612	-	-	0	-	-	@900	-	-	RNP APCH
020	TF	CS611	-	289(289.4)	0	11.13	-	@600	-	-	RNP APCH
030	TF	CS610 (MAPT)	Y	289(289.4)	0	7.05	-	@231	-	-3.00°/15.25	RNP APCH
040	CA	-	-	340(340.0)	0	-	-	+450	-	-	RNP APCH
050	DF	CS522	-	-	0	-	R	-	-	-	RNP APCH
060	TF	CS613	-	109(109.4)	0	12.83	-	+1200	-	-	RNP APCH
070	HM	CS613	-	199(199.5)	0	-	L	+1200	-	-	RNP APCH

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
CS613	199(199.5)	0	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
CS500	080(080.0)	0	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH

3. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
CS500	08°32'36.0"N	106°33'58.0"E
CS522	08°47'46.0"N	106°45'15.0"E
CS610	08°43'02.2"N	106°40'29.2"E
CS611	08°41'46.1"N	106°44'06.6"E
CS612	08°39'46.0"N	106°49'50.0"E
CS613	08°45'27.0"N	106°51'51.0"E
CS614	08°35'01.0"N	106°48'10.0"E
RWY29	08°43'45.29"N	106°38'25.69"E