

1. TABULAR DESCRIPTION

DAN 1M DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	-	-	092(091.0)	+1	-	-	+900	-	3.8	RNP 1
020	DF	PK980	-	-	+1	-	-	-	-	3.8	RNP 1
030	TF	PK982	-	002(001.1)	+1	9.28	-	-	-445	3.8	RNP 1
040	TF	PK984	-	337(335.9)	+1	26.31	-	-2450	-	3.8	RNP 1
050	TF	OMGON	-	002(001.2)	+1	17.09	-	-FL120 +FL100	-	3.8	RNP 1
060	TF	XAQUA	-	011(009.9)	+1	51.83	-	+FL120	-	-	RNP 1
070	TF	VILOT	-	006(004.7)	+1	13.23	-	-	-	-	RNP 1
080	TF	DAN	-	006(004.7)	+1	112.60	-	-	-	-	RNP 1

PATNO 1M DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	-	-	092(091.0)	+1	-	-	+900	-	3.6	RNP 1
020	DF	PK980	-	-	+1	-	-	-	-	3.6	RNP 1
030	TF	PK982	-	002(001.1)	+1	9.28	-	-	-445	3.6	RNP 1
040	TF	PK984	-	337(335.9)	+1	26.31	-	-2450	-	3.6	RNP 1
050	TF	DUGOD	-	306(305.4)	+1	22.70	-	+FL100	-	3.6	RNP 1
060	TF	LATOM	-	001(360.0)	+1	50.59	-	-	-	3.4	RNP 1
070	TF	PATNO	-	003(002.1)	+1	120.20	-	+FL290	-	3.4	RNP 1

CQ 1M DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Min CG (%)	Nav Spec
010	CA	-	-	092(091.0)	+1	-	-	+900	-	3.8	RNP 1
020	DF	PK980	-	-	+1	-	-	-	-	3.8	RNP 1
030	TF	PK982	-	002(001.1)	+1	9.28	-	-	-445	3.8	RNP 1
040	TF	PK984	-	337(335.9)	+1	26.31	-	-2450	-	3.8	RNP 1
050	TF	OMGON	-	002(001.2)	+1	17.09	-	-FL120 +FL100	-	3.8	RNP 1
060	TF	RUXIK	-	044(042.9)	+1	71.50	-	-	-	-	RNP 1
070	TF	CQ	-	026(025.2)	+1	58.86	-	-	-	-	RNP 1