

1. TABULAR DESCRIPTION

DAN 1P ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DAN	-	-	+1	-	-	-	-	RNP 1
020	TF	SADIN	-	182(181.2)	+1	107.66	-	-	-	RNP 1
030	TF	TORUT	-	182(181.2)	+1	71.14	-	+FL130	-	RNP 1
040	TF	PK918	-	191(189.9)	+1	25.67	-	-	-	RNP 1
050	TF	PK916	-	257(256.0)	+1	19.50	-	+2750	-	RNP 1
060	TF	PK914	-	257(256.0)	+1	18.46	-	+2150	-	RNP 1

CQ 1P ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	CQ	-	-	+1	-	-	-	-	RNP 1
020	TF	TALAP	-	206(205.3)	+1	121.98	-	+FL130	-	RNP 1
030	TF	PK918	-	206(205.1)	+1	25.20	-	-	-	RNP 1
040	TF	PK916	-	257(256.0)	+1	19.50	-	+2750	-	RNP 1
050	TF	PK914	-	257(256.0)	+1	18.46	-	+2150	-	RNP 1

PATMA 1C ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	PATMA	-	-	+1	-	-	-	-	RNP 1
020	TF	SADAS	-	002(001.1)	+1	108.84	-	-	-	RNP 1
030	TF	TEDIG	-	002(001.2)	+1	30.28	-	+FL110	-	RNP 1
040	TF	PK913	-	350(349.2)	+1	33.51	-	+2150	-	RNP 1

BMT 1C ARRIVAL										
Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	BMT	-	-	+1	-	-	-	-	RNP 1
020	TF	SADAS	-	337(336.3)	+1	79.01	-	-	-	RNP 1
030	TF	TEDIG	-	002(001.2)	+1	30.28	-	+FL110	-	RNP 1
040	TF	PK913	-	350(349.2)	+1	33.51	-	+2150	-	RNP 1