

1. TABULAR DESCRIPTION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	PK800	–	–	+1	–	–	+1850	–	–	RNP APCH
020	TF	PK913	–	300(299.5)	+1	35.12	–	–	–	–	RNP APCH
030	TF	PK912	–	002(001.0)	+1	12.96	–	@1850	–	–	RNP APCH
040	TF	PK911	–	092(090.9)	+1	12.97	–	@1350	–	–	RNP APCH
050	TF	RWY09 (MAPT)	Y	092(090.9)	+1	11.27	–	@759	–	-3.0/ 15.25	RNP APCH
060	CA	–	–	092(090.9)	+1	–	–	+1100	–	–	RNP APCH
070	DF	PK800	–	–	+1	–	–	@1850	–	–	RNP APCH
080	HM	PK800	–	300(299.0)	+1	–	L	+1850	–	–	RNP APCH

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PK800	300(299.0)	+1	1 ≤ FL140 1.5 > FL140	L	+1850	-425 ≤ FL140 -445 > FL140	RNP APCH

3. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
PK800	13°44'06.0"N	108°03'36.0"E
PK913	13°53'28.0"N	107°46'38.0"E
PK912	14°00'29.5"N	107°46'45.4"E
PK911	14°00'22.8"N	107°53'57.4"E
RWY09	14°00'16.78"N	108°00'12.79"E