

**1. TABULAR DESCRIPTION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	PK800	–	–	+1	–	–	+1850	–	–	RNP APCH
020	TF	PK713	–	047(045.7)	+1	23.59	–	–	–	–	RNP APCH
030	TF	PK712	–	002(000.9)	+1	12.97	–	@1650	–	–	RNP APCH
040	TF	PK711	–	272(271.0)	+1	9.30	–	@1350	–	–	RNP APCH
050	TF	RWY27 (MAPT)	Y	272(271.0)	+1	11.47	–	@749	–	-3.0/ 15.25	RNP APCH
060	CA	–	–	272(271.0)	+1	–	–	+1050	–	–	RNP APCH
070	DF	PK720	–	–	+1	–	–	–	-425	–	RNP APCH
080	TF	PK800	–	132(130.8)	+1	27.46	–	@1850	–	–	RNP APCH
090	HM	PK800	–	047(046.0)	+1	–	R	+1850	–	–	RNP APCH

**2. HOLDING PROCEDURES**

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
PK800	047(046.0)	+1	1 ≤ FL140 1.5 > FL140	R	+1850	-425 ≤ FL140 -445 > FL140	RNP APCH

**3. WAYPOINT LIST**

WAYPOINT ID	COORDINATES (WGS-84)	
PK800	13°44'06.0"N	108°03'36.0"E
PK713	13°53'02.0"N	108°12'58.0"E
PK712	14°00'03.9"N	108°13'04.7"E
PK711	14°00'09.2"N	108°07'54.8"E
RWY27	14°00'15.48"N	108°01'32.76"E
PK720	13°53'50.0"N	107°52'04.0"E