

Procedure coding

1. KUMUN 1A DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	PC800	-	328 (326.7)	+1	-	-	-	-	5.3	RNP 1
2	TF	PC851	-	321 (320.4)	+1	20.9	-	-1850 +1500	-	5.3	RNP 1
3	TF	XUTKA	-	348 (347.2)	+1	31.5	-	-FL120 +2450	-	-	RNP 1
4	TF	PC999	-	011 (009.7)	+1	34.0	-	-	-	-	RNP 1
5	TF	KUMUN	-	348 (347.3)	+1	25.1	-	-	-	-	RNP 1

2. KUMUN 1B DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	PC800	-	328 (326.7)	+1	-	-	-	-390	3.8	RNP 1
2	TF	PC801	-	030 (029.0)	+1	11.7	-	-	-	3.8	RNP 1
3	TF	PC811	-	029 (028.3)	+1	13.1	-	-1850 +1200	-	3.8	RNP 1
4	TF	DOXIS	-	348 (347.3)	+1	31.5	-	-FL120 +2450	-	4.0	RNP 1
5	TF	PC999	-	326 (324.9)	+1	34.0	-	-	-	-	RNP 1
6	TF	KUMUN	-	348 (347.3)	+1	25.1	-	-	-	-	RNP 1

3. KAMGO 1A DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	PC800	-	328 (326.7)	+1	-	-	-	-	5.4	RNP 1
2	TF	PC801	-	030 (029.0)	+1	11.7	-	-	-390	5.4	RNP 1
3	TF	PC821	-	092 (091.0)	+1	15.4	-	@1850	-	5.4	RNP 1
4	TF	PC822	-	149 (148.4)	+1	12.9	-	+2450	-	4.7	RNP 1
5	TF	PC831	-	176 (175.1)	+1	25.1	-	+FL120	-	4.8	RNP 1
6	TF	VINIX	-	190 (189.1)	+1	39.0	-	-	-	-	RNP 1
7	TF	KAMGO	-	217 (215.9)	+1	21.1	-	-	-	-	RNP 1

4. NOBID 1K DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	PC860	-	328 (326.7)	+1	-	-	-	-	4.9	RNP 1
2	TF	PC861	-	264 (262.8)	+1	15.3	-	-1850 +1200	-	4.9	RNP 1
3	TF	PC862	-	201 (200.0)	+1	44.9	-	+FL130	-	6.2	RNP 1
4	TF	NOBID	-	201 (199.9)	+1	38.6	-	-	-	-	RNP 1

5. NOBID 1L DEPARTURE

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Min CG (%)	Nav Spec
1	CF	PC800	-	328 (326.7)	+1	-	-	-	-	5.4	RNP 1
2	TF	PC801	-	030 (029.0)	+1	11.7	-	-	-390	5.4	RNP 1
3	TF	PC821	-	092 (091.0)	+1	15.4	-	@1850	-	5.4	RNP 1
4	TF	PC822	-	149 (148.4)	+1	12.9	-	+2450	-	4.7	RNP 1
5	TF	PC841	-	217 (216.5)	+1	25.6	-	+FL120	-	4.7	RNP 1
6	TF	NINOV	-	217 (216.4)	+1	51.3	-	-	-	-	RNP 1
7	TF	NOBID	-	241 (239.6)	+1	31.4	-	-	-	-	RNP 1