

Procedure coding

1. KUMUN 1D ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	KUMUN	-	-	+1	-	-	-	-	RNP 1
2	TF	VEXIT	-	168 (167.3)	+1	55.1	-	+FL130	-	RNP 1
3	TF	DEMIS	-	168 (167.2)	+1	30.0	-	-	-	RNP 1
4	TF	PC801	-	149 (148.3)	+1	13.5	-	-	-	RNP 1
5	TF	PC732	-	149 (148.4)	+1	12.4	-	@2150	-	RNP 1
6	TF	PC731	-	149 (148.4)	+1	23.7	-	+1200	-390	RNP 1

2. KUMUN 1E ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	KUMUN	-	-	+1	-	-	-	-	RNP 1
2	TF	VEXIT	-	168 (167.3)	+1	55.1	-	+FL130	-	RNP 1
3	TF	DEMIS	-	168 (167.2)	+1	30.0	-	-	-	RNP 1
4	TF	PC801	-	149 (148.3)	+1	13.5	-	-	-	RNP 1
5	TF	PC742	-	209 (208.3)	+1	26.4	-	@2150	-	RNP 1
6	TF	PC711	-	148 (146.7)	+1	23.7	-	-2150 +1500	-390	RNP 1

3. KAMGO 1D ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	KAMGO	-	-	+1	-	-	-	-	RNP 1
2	TF	XIKRA	-	356 (355.1)	+1	14.4	-	-FL110 +FL100	-	RNP 1
3	TF	PC721	-	010 (009.1)	+1	29.2	-	-2150 +1500	-	RNP 1

4. NOBID 1N ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	NOBID	-	-	+1	-	-	-	-	RNP 1
2	TF	SEGTO	-	036 (034.9)	+1	27.0	-	-FL110 +FL100	-	RNP 1
3	TF	PC712	-	057 (056.1)	+1	33.0	-	+1850	-	RNP 1
4	TF	PC711	-	057 (056.1)	+1	9.6	-	-2150 +1500	-390	RNP 1

5. HOLDING PROCEDURES

Holding Fix	Inbound Course/Track °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
VEXIT	168 (167.2)	+1	1 ≤ FL140 1.5 > FL140	L	+FL130	-425 ≤ FL140 -445 > FL140	RNP 1
XIKRA	010 (009.1)	+1	1 ≤ FL140 1.5 > FL140	L	+FL100	-425 ≤ FL140 -445 > FL140	RNP 1
SEGTO	057 (056.1)	+1	1 ≤ FL140 1.5 > FL140	R	+FL100	-425 ≤ FL140 -445 > FL140	RNP 1
PC711	057 (056.1)	+1	1 ≤ FL140 1.5 > FL140	R	+1850	-425 ≤ FL140 -445 > FL140	RNP 1
PC721	010 (009.1)	+1	1 ≤ FL140 1.5 > FL140	R	+1500	-425 ≤ FL140 -445 > FL140	RNP 1
PC731	237 (236.2)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP 1