

1. TABULAR DESCRIPTION

| INITIAL APPROACH | | | | | | | | | | | |
|------------------|-----------------|---------------------|----------|---------------|--------------------|---------------|----------------|--------------|--------------------|---------|----------|
| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed limit (km/h) | VPA/TCH | Nav Spec |
| 010 | IF | AROMU | – | – | +1 | – | – | +1500 | -390 | – | RNP 1 |
| 020 | TF | CA411 | – | 226(224.6) | +1 | 12.96 | – | @900 | – | – | RNP 1 |
| 010 | IF | SOTIN | – | – | +1 | – | – | +1800 | -425 | – | RNP 1 |
| 020 | TF | CA411 | – | 034(032.8) | +1 | 16.52 | – | @900 | – | – | RNP 1 |

| MISSED APPROACH | | | | | | | | | | | |
|-----------------|-----------------|---------------------|----------|---------------|--------------------|---------------|----------------|--------------|--------------------|---------|----------|
| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed limit (km/h) | VPA/TCH | Nav Spec |
| 010 | CF | CA413 | – | 316(314.6) | +1 | – | – | – | – | – | RNP 1 |
| 020 | TF | CA414 | – | 034(033.3) | +1 | 15.00 | – | +800 | – | – | RNP 1 |
| 030 | TF | ATPAD | – | 114(113.0) | +1 | 20.43 | – | @900 | – | – | RNP 1 |
| 040 | HM | ATPAD | – | 159(157.5) | +1 | – | L | +900 | -390 | – | RNP 1 |

2. HOLDING PROCEDURES

| Holding Fix | Inbound Course °M(°T) | Magnetic Variation | Time (min) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|-------------|-----------------------|--------------------|--------------------------|----------------|--------------|------------------------------|----------|
| AROMU | 226(224.6) | +1 | 1 ≤ FL140 1.5 > FL140 | L | +1500 | -390 ≤ FL140 -445 > FL140 | RNP 1 |
| SOTIN | 034(032.6) | +1 | 1 ≤ FL140 1.5 > FL140 | R | +1800 | -425 ≤ FL140 -445 > FL140 | RNP 1 |
| ATPAD | 159(157.5) | +1 | 1 ≤ FL140 1.5 > FL140 | L | +900 | -390 | RNP 1 |

3. WAYPOINT LIST

| WAYPOINT/FIX | COORDINATES (WGS-84) | |
|--|----------------------|----------------|
| AROMU | 15°21'02.3"N | 108°56'09.0"E |
| SOTIN | 15°08'30.0"N | 108°46'04.0"E |
| CA411 - BRG 135.55° ICL LLZ/D11.15 ICL DME | 15°16'02.0"N | 108°51'03.8"E |
| CA412 - BRG 135.55° ICL LLZ/D6.13 ICL DME | 15°19'34.3"N | 108°47'21.8"E |
| RWY32 | 15°23'46.78"N | 108°42'57.62"E |
| CA413 | 15°30'28.3"N | 108°35'57.0"E |
| CA414 | 15°37'16.4"N | 108°40'33.1"E |
| ATPAD | 15°32'56.8"N | 108°51'04.3"E |
| ICL GP/DME | 15°23'56.3"N | 108°42'53.4"E |
| ICL LLZ | 15°25'03.1"N | 108°41'37.7"E |