

**1. TABULAR DESCRIPTION**

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	CM913	-	-	0	-	-	+1200	-	-	RNP APCH
020	TF	CM912	-	181(181.4)	0	11.14	-	+750	-	-	RNP APCH
010	IF	CM800	-	-	0	-	-	+900	-	-	RNP APCH
020	TF	CM914	-	281(280.8)	0	18.53	-	-	-	-	RNP APCH
030	TF	CM912	-	002(001.5)	0	11.11	-	+750	-	-	RNP APCH
010	IF	CM912	-	-	0	-	-	+750	-	-	RNP APCH
020	TF	CM911	-	092(091.5)	0	9.26	-	@450	-	-	RNP APCH
030	TF	RWY09	Y	092(091.5)	0	8.26	-	@17	-	-3.0/ 15.25	RNP APCH
040	CA	-	-	092(091.5)	0	-	-	+300	-	-	RNP APCH
050	DF	CM800	-	-	0	-	R	@900	-	-	RNP APCH
060	HM	CM800	-	281(281.0)	0	-	L	+900	-	-	RNP APCH

**2. HOLDING PROCEDURES**

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
CM913	181(181.0)	0	1 ≤ FL140 1.5 > FL140	R	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH
CM800	281(281.0)	0	1 ≤ FL140 1.5 > FL140	L	+900	-425 ≤ FL140 -445 > FL140	RNP APCH

**3. WAYPOINT LIST**

WAYPOINT ID	COORDINATES (WGS-84)	
CM913	09°16'57.0"N	105°00'51.0"E
CM914	09°04'53.0"N	105°00'32.0"E
CM912	09°10'54.6"N	105°00'41.9"E
CM911	09°10'46.6"N	105°05'45.2"E
RWY09	09°10'39.54"N	105°10'15.78"E
CM800	09°03'00.0"N	105°10'28.0"E