

<b>LEGEND</b>	
CONTROL ZONE (CTR)	---
REPORTING POINT (COMPULSORY)	▲
DEPARTURE/ARRIVAL ROUTING	W18
TRANSIT ROUTING	L637
DISTANCE IN KILOMETRES	30
UPPER/LOWER LIMIT	FL460 900M
MAGNETIC BEARING	210°
RADIO NAVIGATION AID	NAME: CAMAU NAVAID TYPE AND FREQUENCY: NDB 305 IDENTIFICATION: QL COORDINATES: 09°1034'N 105°1036'E
AREA MINIMUM ALTITUDE (AMA)	045
EACH 1° QUADRILATERAL CONTAINS AN AREA MINIMUM ALTITUDE (AMA) WHICH REPRESENTS THE LOWEST ALTITUDE WHICH MAY BE USED UNDER INSTRUMENT METEOROLOGICAL CONDITIONS (IMC). THE AMA PROVIDES A MINIMUM CLEARANCE OF 300 METRES (600 METRES IN MOUNTAINOUS AREAS) ABOVE ALL OBSTACLES IN THE QUADRILATERAL. IT IS REPRESENTED IN THOUSANDS AND TENS OF METRES ABOVE MEAN SEA LEVEL (MSL).	
EXAMPLE: 450 METRES	045

