

1. TABULAR DESCRIPTION

VIN 1S ARRIVAL

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed limit (km/h) | VPA/TCH | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------|--------------------|---------------|----------------|--------------|--------------------|---------|----------|
| 010 | IF | VIN | – | – | +1 | – | – | – | – | – | RNAV 1 |
| 020 | TF | HARON | – | 353(351.8) | +1 | 72.01 | – | @2450 | -415 | – | RNAV 1 |
| 030 | TF | TX527 | – | 008(007.2) | +1 | 9.52 | – | – | – | – | RNAV 1 |
| 040 | TF | TX525 | – | 082(080.9) | +1 | 9.36 | – | – | – | – | RNAV 1 |
| 050 | TF | TX523 | – | 049(048.4) | +1 | 9.36 | – | – | – | – | RNAV 1 |
| 060 | TF | TX521 | – | 017(015.9) | +1 | 9.34 | – | @2450 | – | – | RNAV 1 |
| 070 | TF | TUNPI | – | 271(269.6) | +1 | 16.68 | – | +1850 | – | – | RNAV 1 |

2. HOLDING PROCEDURES

| Holding Fix | Inbound Course °M(°T) | Magnetic Variation | Time (min) | Turn Direction | Altitude (m) | Speed limit (km/h) | Nav Spec |
|-------------|-----------------------|--------------------|--------------------------|----------------|--------------|------------------------------|----------|
| HARON | 008(007.3) | +1 | 1 ≤ FL140 1.5 > FL140 | R | +2450 | -425 ≤ FL140 -445 > FL140 | RNAV 1 |

3. WAYPOINT LIST

| WAYPOINT ID | COORDINATES (WGS-84) | |
|-------------|----------------------|-------------|
| HARON | 19°22'41"N | 105°34'16"E |
| TUNPI | 19°36'46"N | 105°36'10"E |
| TX521 | 19°36'50"N | 105°45'42"E |
| TX523 | 19°31'58"N | 105°44'14"E |
| TX525 | 19°28'36"N | 105°40'14"E |
| TX527 | 19°27'48"N | 105°34'57"E |
| VIN | 18°44'03"N | 105°40'06"E |