

1. TABULAR DESCRIPTION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	VPA/TCH	Nav Spec
010	IF	LUTUT	–	–	+1	–	–	+1200	–	–	RNP APCH
020	TF	TX412	–	220(218.9)	+1	15.96	–	–	-390	–	RNP APCH
030	TF	TX410	–	220(219.0)	+1	12.00	–	@900	–	–	RNP APCH
040	TF	TX404	–	310(308.9)	+1	9.51	–	@550	–	–	RNP APCH
050	TF	RWY31 (MAPT)	Y	310(308.8)	+1	9.93	–	@29	–	-3.00°/15.25	RNP APCH
060	CF	TX741	Y	310(308.8)	+1	–	–	–	–	–	RNP APCH
070	CF	LUTUT	–	083(081.6)	+1	–	R	@1200	-425	–	RNP APCH
080	HM	LUTUT	–	220(218.9)	+1	–	L	+1200	–	–	RNP APCH

2. HOLDING PROCEDURES

Holding Fix	Inbound Course °M(°T)	Magnetic Variation	Time (min)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
LUTUT	220(218.9)	+1	1 ≤ FL140 1.5 > FL140	L	+1200	-425 ≤ FL140 -445 > FL140	RNP APCH

3. WAYPOINT LIST

WAYPOINT ID	COORDINATES (WGS-84)	
LUTUT	19°58'48.0"N	105°47'36.0"E
RWY31	19°53'36.62"N	105°28'52.24"E
TX404	19°50'14.3"N	105°33'18.2"E
TX410	19°47'00.4"N	105°37'32.7"E
TX412	19°52'03.8"N	105°41'52.0"E
TX741	19°55'48.7"N	105°25'58.5"E