


LEGEND											
CONTROL ZONE	(CTR)										
REPORTING POINT	(COMPULSORY)										
ATIS ROUTE	W24										
DISTANCE IN KILOMETRES	30										
MAGNETIC BEARING	354°										
RADIO NAVIGATION AID	<table border="1"> <tr> <td>NAME</td> <td>THOXUAN</td> </tr> <tr> <td>NAV AID TYPE AND FREQUENCY</td> <td>DVOR/DME 114.8</td> </tr> <tr> <td>IDENTIFICATION</td> <td>THX</td> </tr> <tr> <td>COORDINATES</td> <td>19°53'05"N 105°29'34"E</td> </tr> <tr> <td>ELEV OF DME ANTENNA</td> <td>30 m</td> </tr> </table>	NAME	THOXUAN	NAV AID TYPE AND FREQUENCY	DVOR/DME 114.8	IDENTIFICATION	THX	COORDINATES	19°53'05"N 105°29'34"E	ELEV OF DME ANTENNA	30 m
NAME	THOXUAN										
NAV AID TYPE AND FREQUENCY	DVOR/DME 114.8										
IDENTIFICATION	THX										
COORDINATES	19°53'05"N 105°29'34"E										
ELEV OF DME ANTENNA	30 m										
<p>EACH 1° QUADRILATERAL CONTAINS AN AREA MINIMUM ALTITUDE (AMA) WHICH REPRESENTS THE LOWEST ALTITUDE WHICH MAY BE USED UNDER INSTRUMENT METEOROLOGICAL CONDITIONS (IMC). THE AMA PROVIDES A MINIMUM CLEARANCE OF 300 METRES (600 METRES IN MOUNTAINOUS AREAS) ABOVE ALL OBSTACLES IN THE QUADRILATERAL. IT IS REPRESENTED IN THOUSANDS AND TENS OF METRES ABOVE MEAN SEA LEVEL.</p> <p>EXAMPLE: 2250 METRES 225</p>											



20° 00' N

19° 45' N