

# Procedure coding

## 1. RNP RWY 07L: APPROACH FROM SAMDU

RCMD.PATH TERMINATOR	FIX ID (WPT NAME)	FLY- OVER	DISTANCE (km)	TRACK		TURN DIRECTION	ALTITUDE (m)	SPEED LIMIT (IAS) (km/h)	VER ANGLE	NAV SPEC
				MAG TRACK	TRUE TRACK					
IF	SAMDU	-	-	-	-	-	-1500	-425	-	RNP APCH
TF	TS526	-	9.3	025	024.1	-	+600	-	-	RNP APCH
TF	TS524	-	6.5	070	069.1	-	@600	-	-	RNP APCH
TF	RW07L	Y	11.2	070	069.1	-	-	-	-3°	RNP APCH
CF	TS594	-	17.1	070		-	-	-	-	RNP APCH
TF	TS596	-	13.3	160	159.1	-	-	-	-	RNP APCH
TF	TUNBI	-	25.6	190	188.8	-	@900	-425	-	RNP APCH
HM	TUNBI	-	-	001	360.0	L	@900	-405	-	RNP APCH

## 2. RNAV HOLDING PROCEDURE

Holding Fix	Fly- over	Inbound Course/Track °M(°T)		Magnetic Variation	Time (s)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
TUNBI	Y	001	360.0	+1	60	L	@900	-405	RNAV 1