

# Procedure coding

## 1. RWY 07L/R - RNAV 1: XOBAB TWO BRAVO DEPARTURE (XOBAB 2B)

### INITIAL CLIMB RWY 07L

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS812	-	070	+1	11.7	-	-	-	RNAV 1

### INITIAL CLIMB RWY 07R

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS812	-	068	+1	10.5	-	-	-	RNAV 1

### XOBAB 2B CODING FROM TS812

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TS812	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS822	-	139 (138.0)	+1	27.6	-	-2750 +1200	-	RNAV 1
3	TF	TS824	-	229 (228.0)	+1	13.3	-	-3050	-	RNAV 1
4	TF	TS826	-	229 (228.0)	+1	14.9	-	-3650	-	RNAV 1
5	TF	TS828	-	229 (227.9)	+1	9.3	-	+3950	-460	RNAV 1
6	TF	XOBAB	-	188 (187.0)	+1	34.7	-	-	-	RNAV 1

### NIXIV TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	XOBAB	-	-	+1	-	-	-	-	RNAV 1
2	TF	NIXIV	-	182 (180.7)	+1	82.6	-	-	-	RNAV 1

## 2. RWY 07L/R - RNAV 1: MALAY TWO BRAVO DEPARTURE (MALAY 2B)

### INITIAL CLIMB RWY 07L

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS812	-	070	+1	11.7	-	-	-	RNAV 1

### INITIAL CLIMB RWY 07R

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS812	-	068	+1	10.5	-	-	-	RNAV 1

### MALAY 2B CODING FROM TS828

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TS812	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS822	-	139 (138.0)	+1	27.6	-	-2750 +1200	-	RNAV 1
3	TF	TS824	-	229 (228.0)	+1	13.3	-	-3050	-	RNAV 1
4	TF	TS826	-	229 (228.0)	+1	14.9	-	-3650	-	RNAV 1
5	TF	TS828	-	229 (227.9)	+1	9.3	-	+3950	-460	RNAV 1
6	TF	MALAY	-	226 (224.7)	+1	42.3	-	-	-	RNAV 1

### ANHOA TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	MALAY	-	-	+1	-	-	-	-	RNAV 1
2	TF	ANHOA	-	233 (231.7)	+1	70.1	-	-	-	RNAV 1