

# Procedure coding

## 1. RWY 25L/R - RNAV 1: ANTRI TWO DELTA DEPARTURE (ANTRI 2D)

### INITIAL CLIMB RWY 25L

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS612	Y	250	+1	7.1	-	-	-445	RNAV 1
2	DF	TS626	-	-	+1	-	-	+1200	-	RNAV 1

### INITIAL CLIMB RWY 25R

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS614	Y	250	+1	7.2	-	-	-445	RNAV 1
2	DF	TS626	-	-	+1	-	-	+1200	-	RNAV 1

### ANTRI 2D CODING FROM TS626

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TS626	-	-	+1	-	-	+1200	-	RNAV 1
2	TF	TS628	-	070 (069.1)	+1	9.8	-	-2750	-	RNAV 1
3	TF	TS632	-	070 (069.1)	+1	14.8	-	+3050	-	RNAV 1
4	TF	TS814	-	053 (051.5)	+1	32.1	-	-	-	RNAV 1
5	TF	TS816	-	032 (031.3)	+1	17.2	-	-	-	RNAV 1
6	TF	ANTRI	-	032 (031.3)	+1	17.2	-	-	-	RNAV 1

### DOVIN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	ANTRI	-	-	+1	-	-	-	-	RNAV 1
2	TF	DOVIN	-	050 (048.6)	+1	126.6	-	-	-	RNAV 1

### DILIN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	ANTRI	-	-	+1	-	-	-	-	RNAV 1
2	TF	DILIN	-	065 (063.5)	+1	110.0	-	-	-	RNAV 1

### PTH TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	ANTRI	-	-	+1	-	-	-	-	RNAV 1
2	TF	PTH	-	107 (105.7)	+1	94.9	-	-	-	RNAV 1

### PATMA TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	ANTRI	-	-	+1	-	-	-	-	RNAV 1
2	TF	PATMA	-	027 (025.6)	+1	144.2	-	-	-	RNAV 1

## 2. RWY 25L/R - RNAV 1: LANHI TWO DELTA DEPARTURE (LANHI 2D)

### INITIAL CLIMB RWY 25L

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS612	Y	250	+1	7.1	-	-	-445	RNAV 1
2	DF	TS626	-	-	+1	-	-	+1200	-	RNAV 1

### INITIAL CLIMB RWY 25R

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS614	Y	250	+1	7.2	-	-	-445	RNAV 1
2	DF	TS626	-	-	+1	-	-	+1200	-	RNAV 1