

**Procedure coding (cont.)**

**3. RWY 25L/R - RNAV 1: ENPAS TWO DELTA DEPARTURE (ENPAS 2D)**

**INITIAL CLIMB RWY 25L**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Magnetic Course/Track | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|-----------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1             | CF              | TS616               | -        | 250                   | +1                 | 11.7          | -              | -            | -            | RNAV 1   |

**INITIAL CLIMB RWY 25R**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Magnetic Course/Track | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|-----------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1             | CF              | TS616               | -        | 248                   | +1                 | 10.8          | -              | -            | -            | RNAV 1   |

**ENPAS 2D CODING FROM TS616**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1             | IF              | TS616               | -        | -                   | +1                 | -             | -              | -            | -            | RNAV 1   |
| 2             | TF              | TS618               | -        | 250 (249.0)         | +1                 | 26.5          | -              | -3350        | -            | RNAV 1   |
| 3             | TF              | ENPAS               | -        | 215 (214.3)         | +1                 | 38.4          | -              | -            | -            | RNAV 1   |

**ANHOA TRANSITION**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1             | IF              | ENPAS               | -        | -                   | +1                 | -             | -              | -            | -            | RNAV 1   |
| 2             | TF              | ANHOA               | -        | 199 (198.2)         | +1                 | 71.3          | -              | -            | -            | RNAV 1   |

**4. RWY 25L/R - RNAV 1: XOBAB TWO DELTA DEPARTURE (XOBAB 2D)**

**INITIAL CLIMB RWY 25L**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Magnetic Course/Track | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|-----------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1             | CF              | TS616               | -        | 250                   | +1                 | 11.7          | -              | -            | -            | RNAV 1   |

**INITIAL CLIMB RWY 25R**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Magnetic Course/Track | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|-----------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1             | CF              | TS616               | -        | 248                   | +1                 | 10.8          | -              | -            | -            | RNAV 1   |

**XOBAB 2D CODING FROM TS616**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1             | IF              | TS616               | -        | -                   | +1                 | -             | -              | -            | -            | RNAV 1   |
| 2             | TF              | TS641               | -        | 172 (171.2)         | +1                 | 27.8          | -              | -2750        | -            | RNAV 1   |
| 3             | TF              | TS642               | -        | 172 (171.2)         | +1                 | 13.0          | -              | -3350        | -            | RNAV 1   |
| 4             | TF              | TS644               | -        | 172 (171.3)         | +1                 | 21.9          | -              | -4250        | -            | RNAV 1   |
| 5             | TF              | XOBAB               | -        | 165 (164.4)         | +1                 | 8.3           | -              | -            | -            | RNAV 1   |

**NIXIV TRANSITION**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1             | IF              | XOBAB               | -        | -                   | +1                 | -             | -              | -            | -            | RNAV 1   |
| 2             | TF              | NIXIV               | -        | 182 (180.7)         | +1                 | 82.6          | -              | -            | -            | RNAV 1   |

**5. RWY 25L/R - RNAV 1: MISAN TWO DELTA DEPARTURE (MISAN 2D)**

**INITIAL CLIMB RWY 25L**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Magnetic Course/Track | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|-----------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1             | CF              | TS616               | -        | 250                   | +1                 | 11.7          | -              | -            | -            | RNAV 1   |

**INITIAL CLIMB RWY 25R**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Magnetic Course/Track | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|-----------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1             | CF              | TS616               | -        | 248                   | +1                 | 10.8          | -              | -            | -            | RNAV 1   |

**MISAN 2D CODING FROM TS616**

| Serial number | Path Descriptor | Waypoint Identifier | Fly-over | Course/Track °M(°T) | Magnetic Variation | Distance (km) | Turn Direction | Altitude (m) | Speed (km/h) | Nav Spec |
|---------------|-----------------|---------------------|----------|---------------------|--------------------|---------------|----------------|--------------|--------------|----------|
| 1             | IF              | TS616               | -        | -                   | +1                 | -             | -              | -            | -            | RNAV 1   |
| 2             | TF              | TS618               | -        | 250 (249.0)         | +1                 | 26.5          | -              | -3350        | -            | RNAV 1   |
| 3             | TF              | MISAN               | -        | 232 (231.2)         | +1                 | 36.3          | -              | -            | -            | RNAV 1   |