

Procedure coding

1. RWY 25L/R - RNAV 1: TANOS TWO ECHO DEPARTURE (TANOS 2E)

INITIAL CLIMB RWY 25L

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1

INITIAL CLIMB RWY 25R

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (NM)	Turn Direction	Altitude (FT)	Speed (km/h)	Nav Spec
1	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1

TANOS 2E CODING FROM TS616

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
2	TF	TS618	-	250 (249.0)	+1	26.5	-	-3350	-	RNAV 1
3	TF	TS622	-	253 (251.6)	+1	27.8	-	-	-	RNAV 1
4	TF	TS624	-	163 (161.5)	+1	22.2	-	-	-500	RNAV 1
5	TF	TS626	-	067 (066.1)	+1	59.9	-	-	-	RNAV 1
6	TF	TS628	-	070 (069.1)	+1	9.8	-	+FL200	-	RNAV 1
7	TF	TS632	-	070 (069.1)	+1	14.8	-	-	-	RNAV 1
8	TF	TANOS	-	091 (090.0)	+1	52.6	-	-	-	RNAV 1

DOVIN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TANOS	-	-	+1	-	-	-	-	RNAV 1
2	TF	DOVIN	-	034 (032.7)	+1	158.1	-	-	-	RNAV 1

DILIN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TANOS	-	-	+1	-	-	-	-	RNAV 1
2	TF	DILIN	-	043 (042.1)	+1	132.6	-	-	-	RNAV 1

PTH TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TANOS	-	-	+1	-	-	-	-	RNAV 1
2	TF	PTH	-	075 (073.9)	+1	85.2	-	-	-	RNAV 1