

## Procedure coding (cont.)

### TRN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	MISAN	-	-	+1	-	-	-	-	RNAV 1
2	TF	TRN	-	222 (220.7)	+1	57.9	-	-	-	RNAV 1

### 6. RWY 25L/R - RNAV 1: SAPEN TWO DELTA DEPARTURE (SAPEN 2D)

#### INITIAL CLIMB RWY 25L

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS616	-	250	+1	11.7	-	-	-	RNAV 1

#### INITIAL CLIMB RWY 25R

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	CF	TS616	-	248	+1	10.8	-	-	-	RNAV 1

#### SAPEN 2D CODING FROM TS616

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Magnetic Course/Track	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed (km/h)	Nav Spec
1	IF	TS616	-	-	+1	-	-	-	-	RNAV 1
2	TF	SAPEN	-	307 (305.9)	+1	47.2	-	-4250	-	RNAV 1