

ILS W approach procedure for RWY 07R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	80	800	1 100
	D	85	900	1 200

ILS W approach procedure for RWY 07R in case of GP unserviceable	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	145		2 400

ILS W approach procedure for RWY 25L/R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	95	700	1 100
	D	100	800	1 200

ILS W approach procedure for RWY 25L/R in case of GP unserviceable	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C, D	145	1 500	2 100

2. VOR approach procedures

VOR approach procedure for RWY 25L	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B, C	155		2 000
	D	155		2 800

VOR approach procedure for RWY 25R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility(M)
	A, B, C, D	145		2 800

VOR approach procedure for RWY 07L	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	145		2 000
	C, D	145		2 300

VOR approach procedure for RWY 07R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	145		2 000
	C, D	145		2 300

Circling for RWY 07R/L and 25L/R	ACFT CAT	Ceiling (M)	RVR (M)	Visibility (M)
	A, B	190		2 400
	C	290		4 400
D	290		4 800	