

1. TABULAR DESCRIPTION

DALAP 2G ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DALAP	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS548	-	219 (218.1)	+1	34.1	-	-	-	RNAV 1
030	TF	TS546	-	263 (262.3)	+1	43.5	-	+3350	-460	RNAV 1
040	TF	TS544	-	229 (228.0)	+1	5.6	-	+3050	-	RNAV 1
050	TF	ENROP	-	229 (227.9)	+1	17.9	-	@2150	-	RNAV 1
060	TF	TS542	-	217 (216.3)	+1	6.3	-	-	-	RNAV 1
070	TF	TS538	-	242 (241.3)	+1	14.5	-	-	-	RNAV 1
080	TF	TS536	-	277 (276.3)	+1	14.5	-	-	-	RNAV 1
090	TF	TS534	-	312 (311.3)	+1	14.5	-	@2150	-	RNAV 1
100	TF	SAMDU	-	060 (058.8)	+1	24.1	-	-1500	-425	RNAV 1

RINKU TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DOVIN	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS918	-	135 (134.2)	+1	26.5	-	-	-	RNAV 1
030	TF	TS916	-	147 (146.2)	+1	26.5	-	-	-	RNAV 1
040	TF	TS914	-	159 (158.3)	+1	26.5	-	-	-	RNAV 1
050	TF	TS912	-	171 (170.3)	+1	26.5	-	-	-	RNAV 1
060	TF	RINKU	-	183 (181.9)	+1	24.7	-	-	-	RNAV 1
070	TF	DALAP	-	278 (277.4)	+1	127.0	-	-	-	RNAV 1

DOVIN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DOVIN	-	-	+1	-	-	-	-	RNAV 1
020	TF	DALAP	-	219 (218.2)	+1	127.0	-	-	-	RNAV 1

VETOM TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	VETOM	-	-	+1	-	-	-	-	RNAV 1
020	TF	DALAP	-	226 (224.6)	+1	34.0	-	-	-	RNAV 1

PTH TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	PTH	-	-	+1	-	-	-	-	RNAV 1
020	TF	DALAP	-	278 (277.3)	+1	75.2	-	-	-	RNAV 1