

SAPEN 2H ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	SAPEN	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS498	-	139 (137.8)	+1	43.1	-	+4550	-	RNAV 1
030	TF	TS496	-	139 (137.8)	+1	7.4	-	+4250	-	RNAV 1
040	TF	NOKUM	-	139 (137.8)	+1	14.8	-	+3650	-	RNAV 1
050	TF	TS492	-	113 (111.9)	+1	13.0	-	+3050	-	RNAV 1
060	TF	LETRO	-	113 (111.9)	+1	18.1	-	@2150	-460	RNAV 1
070	TF	VANLI	-	077 (075.9)	+1	14.4	-	-	-	RNAV 1
080	TF	TS488	-	069 (068.5)	+1	14.8	-	-	-	RNAV 1
090	TF	RUNSI	-	055 (053.5)	+1	6.4	-	@2150	-	RNAV 1
100	TF	TS458	-	044 (043.0)	+1	8.5	-	-	-	RNAV 1
110	TF	TS456	-	029 (027.9)	+1	12.9	-	-	-	RNAV 1
120	TF	TS454	-	011 (009.8)	+1	12.9	-	@2150	-	RNAV 1
130	TF	SOKAN	-	272 (270.7)	+1	40.7	-	-1500 +730	-425	RNAV 1

VICAL 3H ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	VICAL	-	-	+1	-	-	-	-	RNAV 1
020	TF	LETRO	-	017 (016.3)	+1	38.1	-	@2150	-460	RNAV 1
030	TF	VANLI	-	077 (075.9)	+1	14.4	-	-	-	RNAV 1
040	TF	TS488	-	069 (068.5)	+1	14.8	-	-	-	RNAV 1
050	TF	RUNSI	-	055 (053.5)	+1	6.4	-	@2150	-	RNAV 1
060	TF	TS458	-	044 (043.0)	+1	8.5	-	-	-	RNAV 1
070	TF	TS456	-	029 (027.9)	+1	12.9	-	-	-	RNAV 1
080	TF	TS454	-	011 (009.8)	+1	12.9	-	@2150	-	RNAV 1
090	TF	SOKAN	-	272 (270.7)	+1	40.7	-	-1500 +730	-425	RNAV 1

NIXIV TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	NIXIV	-	-	+1	-	-	-	-	RNAV 1
020	TF	VICAL	-	010 (008.7)	+1	84.3	-	-	-	RNAV 1