

1. TABULAR DESCRIPTION

DALAP 2H ARRIVAL

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DALAP	-	-	+1	-	-	@3350	-460	RNAV 1
020	TF	VIKEP	-	254 (253.3)	+1	18.3	-	@2750	-	RNAV 1
030	TF	TS452	-	173 (172.0)	+1	11.2	-	-	-	RNAV 1
040	TF	TS438	-	191 (189.8)	+1	11.7	-	-	-	RNAV 1
050	TF	TS436	-	209 (208.0)	+1	11.7	-	-	-	RNAV 1
060	TF	TS434	-	229 (227.5)	+1	13.5	-	-	-	RNAV 1
070	TF	TS432	-	250 (248.5)	+1	13.5	-	@2750	-	RNAV 1
080	TF	SOKAN	-	350 (349.0)	+1	37.0	-	-1500 +730	-425	RNAV 1

RINKU TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DOVIN	-	-	+1	-	-	-	-	RNAV 1
020	TF	TS918	-	135 (134.2)	+1	26.5	-	-	-	RNAV 1
030	TF	TS916	-	147 (146.2)	+1	26.5	-	-	-	RNAV 1
040	TF	TS914	-	159 (158.3)	+1	26.5	-	-	-	RNAV 1
050	TF	TS912	-	171 (170.3)	+1	26.5	-	-	-	RNAV 1
060	TF	RINKU	-	183 (181.9)	+1	24.7	-	-	-	RNAV 1
070	TF	DALAP	-	278 (277.4)	+1	127.0	-	@3350	-460	RNAV 1

DOVIN TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	DOVIN	-	-	+1	-	-	-	-	RNAV 1
020	TF	DALAP	-	219 (218.2)	+1	127.0	-	@3350	-460	RNAV 1

VETOM TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	VETOM	-	-	+1	-	-	-	-	RNAV 1
020	TF	DALAP	-	226 (224.6)	+1	34.0	-	@3350	-460	RNAV 1

PTH TRANSITION

Serial number	Path Descriptor	Waypoint Identifier	Fly-over	Course °M(°T)	Magnetic Variation	Distance (km)	Turn Direction	Altitude (m)	Speed limit (km/h)	Nav Spec
010	IF	PTH	-	-	+1	-	-	-	-	RNAV 1
020	TF	DALAP	-	278 (277.3)	+1	75.2	-	@3350	-460	RNAV 1